

HIOKI · LUX METERS · DATASHEET

Hioki FT3425 Lux Meter 200,000 Lux

Model FT3425



Advanced lux meter with 0–200,000 lux range and built-in Bluetooth for wireless data logging via Gennect Cross. Silicon photodiode, JIS Class AA / DIN Class B, $\pm 2\%$ linearity. USB output and memory. For illuminance surveys.

Price and availability

Ask Industrial Supply Syndicate for the current price, stock and a quotation with GST and freight. Call +91 89610 89611 or WhatsApp +91 89610 89611.

Key Features

- Measurement range 20.00 lx to 200,000 lx (5 ranges)
- Silicon photodiode light-receiving element
- JIS C 1609-1 General Class AA and DIN 5032-7 Class B compliant
- $\pm 2\%$ linearity
- Built-in Bluetooth 4.0LE with Gennect Cross app support
- Memory (up to 99 readings), hold, timer hold and zero adjustment
- D/A output and USB2.0 interface
- LR6 alkaline battery $\times 2$ or USB bus power, approx. 300 hours

Order or ask for a quotation

Industrial Supply Syndicate supplies the Hioki FT3425 across India with a GST invoice. Tell us the quantity and delivery location; we reply with a quotation or proforma invoice including freight.

Phone **+91 89610 89611**
WhatsApp **+91 89610 89611**
Email **info@hiokimeters.com**
Online **hiokimeters.com/product/ft3425-lux-meter/**
Address 54, Ezra Street,, Kolkata – 700 001, West Bengal, India
GSTIN 19ACDPC1843J1ZR



Scan to WhatsApp us