

HIOKI · PHASE DETECTORS · DATASHEET

Hioki PD3129 Phase Detector

Model PD3129



Non-contact phase sequence detector for thin insulated conductors (Φ2.4–17mm). Clips onto covered cables to verify 3-phase rotation, 70–600V AC. LED and buzzer indication, live-line check. CAT IV 600V. For motor and panel work.

Price and availability

Ask Industrial Supply Syndicate for the current price, stock and a quotation with GST and freight. Call +91 89610 89611 or WhatsApp +91 89610 89611.

Key Features

- Non-contact phase-sequence detection on insulated wiring
- For thin conductors: Φ2.4mm to 17mm
- Voltage range 70 to 600V AC (continuous sine wave)
- Frequency range 45Hz to 66Hz
- Positive: 4 LEDs light clockwise with intermittent buzzer and green arrow
- Negative: 4 LEDs light counter-clockwise with continuous buzzer
- Live-line check and battery-check functions
- CAT IV 600V safety rating; AA (LR6) ×2, up to 200 hours

Order or ask for a quotation

Industrial Supply Syndicate supplies the Hioki PD3129 across India with a GST invoice. Tell us the quantity and delivery location; we reply with a quotation or proforma invoice including freight.

Phone **+91 89610 89611**
WhatsApp **+91 89610 89611**
Email **info@hiokimeters.com**
Online **hiokimeters.com/product/pd3129-phase-detector/**
Address **54, Ezra Street,, Kolkata – 700 001, West Bengal, India**
GSTIN **19ACDPC1843J1ZR**



Scan to WhatsApp us